

## ASMODAS DOORS MAINTENANCE & CLEANING GUIDE

*Regular maintenance of your Asmodas Door is necessary for smooth performance, good functionality and increasing the life of your door.*

### GENERAL INFORMATION

Doors are a mechanical device and like any other mechanical device they need regular preventive maintenance. All type of doors should be lubricated and cleaned at least twice a year for a normal maintenance.

The relative humidity of the doors in the premises where they are kept, can't exceed 60%. The manufacturer does not assume responsibility for deformation, deflection, bulging of the door decoration panels; hardware, painted metal parts and hinges due to insufficient ventilation of rooms or excessive relative humidity of the air. There must be no chemical activity in the premises where doors is kept.

### CYLINDER CARE

- Lock and unlock cylinder with undamaged key.
- Always be sure to push the key in until it hits the striker.
- Never turn the key forcefully, it must turn easily.
- Open the door with the door handle, not by pulling turned key.
- Twice a year spray cylinder with lubricant to perform its maintenance. An improperly use of the lubricant may damage the cylinder. Consult a cylinder manufacturer for more specific maintenance.
- Do not wash the cylinders with any chemical cleaners
- Do not paint any cylinder surfaces.
- Do not open the door with a detached locking tab.

Door surfaces has to be cleaned with wet cloth, without the use of gasoline, acetone or other active detergents. Do not stick insulating PVC or paper strips on the door.

When electrical, alarm system or other installation work is done through the door frame, door leaf must be open.

When any type of electrical work is done, safety requirements must be observed.

### LOCK CARE

- Do not drill thought the lock.
- Do not paint on the front plate or any other details of lock.
- We recommend to lubricate locks latch bolt once a year with standard oil.

### HINGES CARE

- For outdoor use hinges must be lubricated with special non-rust bearing lubricant.

### BASIC DOOR CARE

- The place in which the doors are installed must be periodically ventilated.
- Liquids can't get on door gaskets.
- It is forbidden to open the door if underneath them there are any hard objects.
- It is forbidden to place any objects in the door openings or fill them with liquid.

### DOOR SURFACE CLEANING INSTRUCTION

Door surface	Soft cloth	Polishing wax	Washing (with or without soap)	Stiff surfaces cloth	Cleaning with wet (mild) cloth	Various household cleaners	Natural fiber fabric
Veneer	+	+	-	-	+	-	+
Painted	+	-	-	-	+	-	+
Laminated	+	+	-	-	+	-	+
Combined	+	-	-	-	+	-	+

**CAUTION:** Never use abrasive or solvent type cleaners like turpentine, petrol, kerosene or paint thinners to clean door surfaces as it may ruin the finish.

DPI-02 Asmodas doors maintenance & cleaning guide / Valid from: 2018.04.27 / Renewed: 2020.07.01